



CE 2032
Heidelberg Materials Devnya Industrial zone 9160, Devnya, Bulgaria www.heidelbergmaterials.bg
14
HMD/CPR-08/01 2032-CPR-19.55D
EN 13282-1:2013 Hydraulic Road Binder BDS EN 13282-1 – HRB E 2
Treatment of materials for bases, sub-bases, capping layers and earthworks roads, railways, airports and other types of infrastructures
Essential characteristics are accessed in accordance with BDS EN 13282-1:2013

DECLARATION OF PERFORMANCE
HMD/CPR-08/01

relative to weighing note №
«kno» / «date»

1. Unique identification code of the product type:

Hydraulic Road Binder – HRB E 2

2. Commercial name

Hydraulic Road Binder – HRB E 2

3. Type

Treatment of materials for bases, sub-bases, capping layers and

**4. Intended use/es of the construction product in accordance
with the applicable harmonized technical specification**

earthworks roads, railways, airports and other types of

infrastructures

5. Manufacturer:

Heidelberg Materials Devnya, Industrial zone 9160, Devnya, Bulgaria,

6. System of assessment and verification of constancy of
performance of the construction product

www.heidelbergmaterials.bg

7. Harmonized standard

System 2+

8. Notified body

Notified body for product certification NB 2032

(2032, Building Research Institute NISI), carried out the product type determination based on type testing (including sampling), the initial inspection of the manufacturing plant and factory production control, continuous monitoring, evaluation and assessment of factory production control and audit-testing of samples taken before placing the product on the market under System 1+ and issued a certificate of constancy of performance, number: 2032-CPR-19.55C

9. Declared performance

Essential characteristics	Performance parameter	Harmonized technical specification
Rapid setting Hydraulic Road Binder	HRB E2	BDS EN 13282-1:2013
Compressive strength	early 7d	≥ 5 MPa
	standard 28d	
Setting time	≥ 90 min	BDS EN 196-1
Soundness-Expansion	≤ 10 mm	
Fineness (sieve residue on 90 microns)	≤ 15%	BDS EN 196-3
Sulphates (SO ₃) content	≤ 4.0 %	BDS EN 196-6
Chloride content	≤ 0.10 %	
Determination of dangerous substances	≤ 2 ppm*	BDS EN 196-2
The content of soluble chromium VI		
		BDS EN 196-10

* Does not apply to cements and cement-containing mixtures that are used in controlled, closed and fully automated processes where the cement and cement-containing mixtures are processed entirely by machines and where there is no possibility of skin contact. For products containing an additive that reduces the content of water-soluble chromium Cr 6+ according to Regulation (EC) 1907/2006, the manufacturer indicates the period of effectiveness of the additive in compliance with the cement storage conditions. This term for cement in bags is up to 3 months from the packaging date indicated on the packaging and up to 1 month from the date of sale for bulk cement.

Signed for and on behalf of the manufacturer by:
Devnya, 29.07.2025

Nadezhda Chankova
Quality Manager